



27	FFZ75-3.5-17	Stud	14	1045		
26	SY5279.2-91	Nut	28	1045		
25	FFZ75-3.5	Bolt	28	4140		
24	FFZ75-3.5	Gasket	1	1010		
23	FFZ75-3.5-16	Protect flange	1	1045		
22	SY5279.2-91	Nut	56	1045		
21	FFZ75-3.5	Bolt	28	4140		
20	FFZ75-3.5	Gasket	1	1010		
19	FFZ75-3.5-15	Plug	1	1045		
18	FFZ75-3.5-14	Crossover sub	1	1045		
17	FFZ75-3.5-13	Lower sealing ring of piston	1	ASSY		
16	FFZ75-3.5-12	O-ring	1	NBR		
15	GB70-85	Stud	20	1045		
14	FFZ75-3.5-11	Piston inner sealing ring	2	NBR		
13	FFZ75-3.5-10	housing	1	4130		
12	FFZ75-3.5-09	Body sleeve	1	4130		
11	FFZ75-3.5-08	Check valve assembly	4	ASSY		
10	FFZ75-3.5-07	Taper piston	1	4130		
9	FFZ75-3.5-06	Upper seal ring of piston	1	NBR		
8	FFZ75-3.5-05	Conical rubber core	1	ASSY		
7	FFZ75-3.5-04	Abrasion proof plate	1	1045		
6	GB5783-86	Stud	16	1045		
5	FFZ75-3.5-03	O-ring	1	NBR		
4	Q/2B223-77	Plug	1	1045		
3	GB5783-86	Stud	12	1045		
2	FFZ75-3.5-02	Compression ring	1	1045		
1	FFZ75-3.5-01	Top cover	1	4130		
No.	Drawing No.	Name	Qty.	Material	Weight	Remark

Mark		Engineering Instruction	Modify By	Date	 建湖县杰林石化机械有限公司 Jianhu Jielin Petrochemical Machinery Co., Ltd					
Change Record										
Unless Otherwise Specified										
1. All dimensions are in mm	Undeclared Tolerance	DWG Type	Designed	ASSY			Diverter assy			
	Tolerance	Parts DWG	Checked							
2. All edge breaks 0.25-0.75 or 45°	X ±0.5	Material See BOM	Examined				FFZ75-3.5-00			
	X.XX ±0.13		Process							
	Angle ±0.5°	Surface Finish See BOM	Approved	DWG Mark	Qty	Weight				Ratio
	0.25 T.L.R		Date	S						
Paper : A3 REV: Sheet1/1										